

SnowHogg II

Specifications

Engine		
	Engine Type	4-Stroke, Single Cylinder, Air Cooled
	Model	GX390 with a 2 year warranty
	Horsepower	13HP
	Clutch	25 HP Electric (rated)
	Starter	Electric with auxiliary recoil
Dimensions		
	Width	50"
	Height	20"
	Depth	51" Note: Depth is from front of blower housing to front of push tube.
Blower		
	Stages	2
	First Stage	Two 17" steel, shaft driven augers.
	Second Stage	Single 16" steel, shaft driven fan.
	Drive Shafts	Bearing supported, with grease zerts.
	Shear Pins	2 first stage (1 per side) augers, 1 second stage, fan.
	Housing	Reinforced steel with a one year warranty.
	Wear Bar	Made of Steel, replaceable.
	Gear Box	Worm gear, with hypoid oil
	Chute	210° rotation range, 70° elevation range
Drive		
	Belts	2
	Belt Type	3/8" V-Belts, universally replaceable
Carriage		
	Push Tube	Adjustable to fit any 4x4 ATV
	Sway Chains	2 both adjustable
	Skis	360° of rotation for easy steering.

All information contained within this text is Copyright of May's Trail Equipment and Leasing L.L.C., and May's Honda Sales. Do not distribute without written permission.