

SnowHogg

Specifications

<u>ENGINE</u>		
	<u>Engine type</u>	<u>4-Stroke, Single Cylinder, Air Cooled</u>
	<u>Model</u>	<u>GX390</u>
	<u>Horsepower</u>	<u>13hp</u>
	<u>Clutch</u>	<u>25hp Electric (rated)</u>
	<u>Starter</u>	<u>Electric with auxiliary recoil</u>
<u>DIMENSIONS</u>		
	<u>Width</u>	<u>42"</u>
	<u>Height</u>	<u>20"</u>
	<u>Depth</u>	<u>51" Note: Depth is from front of blower housing to front of push tube.</u>
<u>BLOWER</u>		
	<u>Stages</u>	<u>2</u>
	<u>First Stage</u>	<u>Two 17" Steel shaft driven augers.</u>
	<u>Second Stage</u>	<u>Single 15" Steel shaft driven fan.</u>
	<u>Drive shafts</u>	<u>Bearing supported, with grease zerts.</u>
	<u>Shear pins</u>	<u>2 first stage (1 per side), 1 second stage. Note: shear pins are a Honda replaceable part.</u>
	<u>Housing</u>	<u>Reinforced Steel with a one year warranty.</u>
	<u>Wear bar</u>	<u>Made of Steel, replaceable</u>
	<u>Gear box</u>	<u>Worm gear, with hypoid oil.</u>
	<u>Chute</u>	<u>210° Rotation range, 70° Elevation range</u>
<u>Drive</u>		
	<u>Belts</u>	<u>2</u>
	<u>Belt type</u>	<u>3/8" V-Belt, universally replaceable</u>
<u>Carriage</u>		
	<u>Push tube</u>	<u>Adjustable to fit any 4x4</u>
	<u>Sway chains</u>	<u>2 Both adjustable</u>
	<u>Shoes</u>	<u>360° of rotation for easy steering</u>

All information contained within this text is Copyright of May's Trail Equipment and Leasing L.L.C., and May's Honda Sales. Do not distribute or copy without written permission.